

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

20

LOC

DIST

REVISIONS

© COPYRIGHT 20

BY -

ALL RIGHTS RESERVED.

GP

00

P

LTR

DESCRIPTION

DATE

DWN

APVD

A

RELEASED

26 JUL 2011

RG

DO

End view of the shoulder screw. The diameter is  $\varnothing .500$  inches. The slot width is  $.050$  inches.

Side view of the shoulder screw. Dimensions include a length of  $.275 \pm .002$  inches, a shoulder length of  $.200$  inches, a base length of  $.150$  inches, and a diameter of  $\varnothing .295$  inches. The thread is M4 X 0.7 THD.


1 MATERIAL: STAINLESS STEEL

2 FINISH: PASSIVATE

3. ITEMS PROVIDED TO THIS SPECIFICATION TO BE PERMANENTLY IDENTIFIED ON THE CONTAINER WITH THE FOLLOWING:  
TE PART NO. AND DATE CODE

2085844-1

PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN R. GRZYBOWSKI 26 JUL 2011	 TE Connectivity													
DIMENSIONS: INCHES		CHK D. ORRIS 26 JUL 2011														
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD D. ORRIS 26 JUL 2011	NAME SHOULDER SCREW .500 DIA SLOTTED HEAD, M4 X 0.7 THD IN-LINE QUAD POWER													
<table border="1"> <tr> <td>0 PLC</td> <td>±-</td> </tr> <tr> <td>1 PLC</td> <td>±-</td> </tr> <tr> <td>2 PLC</td> <td>±.01</td> </tr> <tr> <td>3 PLC</td> <td>±.005</td> </tr> <tr> <td>4 PLC</td> <td>±-</td> </tr> <tr> <td>ANGLES</td> <td>±-</td> </tr> </table>		0 PLC	±-	1 PLC	±-	2 PLC	±.01	3 PLC	±.005	4 PLC	±-	ANGLES	±-	PRODUCT SPEC -	SIZE A3	
0 PLC	±-															
1 PLC	±-															
2 PLC	±.01															
3 PLC	±.005															
4 PLC	±-															
ANGLES	±-															
MATERIAL 1		APPLICATION SPEC -	CAGE CODE 300779	DRAWING NO C-2085844												
FINISH 2		WEIGHT -	RESTRICTED TO -													
		CUSTOMER DRAWING	SCALE 4:1	SHEET 1 OF 1												
			REV A													

1470-19 (3/11)

Pro/ENGINEER DRAWING