BGA Heat Sink - High Performance Straight Fin w/Thermal Tape





ATS Part#:

Description:

ATS-54170K-C1-R0

17.00 x 17.00 x 14.50 mm BGA Heat Sink - High Performance Straight Fin w/Thermal Tape

Heat Sink Type: Heat Sink Attachment: Equivalent Part Number: ATS-54170K-C2-R0

Straight Fin **Thermal Tape**

*Image above is for illustration purpose only.

Features & Benefits

- High aspect ratio, straight fin heat sinks that are ideal for compact PCB environments •
- Designed specifically for BGAs and other surface mount packages .
- Comes preassembled with high performance thermal interface material .

Thermal Performance

AIR VELOCITY		@200 LFM 1.0 M/S	@300 LFM 1.5 M/S	@400 LFM 2.0 M/S	@500 LFM 2.5 M/S	@600 LFM 3.0 M/S	@700 LFM 3.5 M/S	@800 LFM 4.0 M/S
THERMAL RESISTANCE	Unducted Flow	13.1 °C/W	10.4 °C/W	9 °C/W	8.1 °C/W	7.4 °C/W	6.9 °C/W	6.5 °C/W
	Ducted Flow	7.8	N/A	N/A	N/A	N/A	N/A	N/A

Product Detail

Schematic Image	Dimension A	Dimension B	Dimension C	Dimension D	ТІМ	Finish
	17.00 mm	17.00 mm	14.50 mm	N/A mm	T412	BLACK-ANODIZED
■ Integer above is for illustration purpose only.	 Dimension ATS-5417 (Saint-Go Thermal p application ATS resent performant ATS certifier 	bain C675). performance data ar n. rves the right to upd	neight from the botto act heat sink assem e provided for refere ate or change its pro-	bly with an equivale ence only. Actual pe oducts without notic S-6 and REACH coi	rformanc e to impr	al interface material e may vary by

For more information, to find a distributor or to place an order, please contact us at 781-769-2800 (North America), sales@qats.com or www.qats.com.



© 2013 Advanced Thermal Solutions, Inc. | 89-27 Access Road | Norwood MA | 02062 | USA