

(2.54 mm) .100"

SSW SERIES

SMT .025" SQ POST SOCKET

SPECIFICATIONS

For complete specifications and recommended PCB layouts see www.samtec.com?SSW

Insulator Material: Black LCP

Contact Material: Phosphor Bronze

Plating: Au or Sn over

50 μ" (1.27 μm) Ni

Current Rating (SSW/TSM): 4.7 A per pin

(1 pin powered per row)

Operating Temp Range: -55 °C to +125 °C with Gold

-55 °C to +105 °C with Tin

Insertion Depth: (3.68 mm) .145" to (6.35 mm) .250"


Max Cycles: 100 with 10 μ" (0.25 μm) Au

Voltage Rating: 465 VAC / 655 VDC

RoHS Compliant: Yes

Mates With:

TSW, MTSW, HTSW, HMTSW, MTLW, EW, ZW, TSS, HTSS, ZSS, TSM, TSSH, DW, HW



Tiger Buy™ contacts

PROCESSING

Lead-Free Solderable: Yes

SMT Lead Coplanarity: (0.10 mm) .004" max

RECOGNITIONS


For complete scope of recognitions see www.samtec.com/quality



ALSO AVAILABLE (MOQ Required)

- Other platings
- Notch option
- Contact Samtec.

Note: Some lengths, styles and options are non-standard, non-returnable.



Due to technical progress, all designs, specifications and components are subject to change without notice.

WWW.SAMTEC.COM

All parts within this catalog are built to Samtec's specifications. Customer specific requirements must be approved by Samtec and identified in a Samtec customer-specific drawing to apply.